

Safety data sheet

According to 91/155 EEC

Printing date 08.03.2013

Vers.-Nr: 43

Revision: 02.01.2013

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Transpoxy Finish 4.60 pack B
- **Article number:** 460b
- **Application of the substance/preparation:**
Epoxy curing agent
Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:** Wagon Paints Australia P/L 5 Stephenson Rd Bayswater North 3153
- **Emergency telephone number:** (03) 9729 1344 from 8.00 am to 4.30 pm

2 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

68410-23-1	reaction product based on fatty acids and polyethyleneamine ⚠ H318	50-100%
1330-20-7	xylene, mixture of isomers ⚠ H226; ⚠ H312; H332; H315	25-50%

3 Hazards identification

- **Classification of the substance or mixture**



GHS02 flame

H226 Flammable liquid and vapour.



GHS05 corrosion

H318 Causes serious eye damage.



GHS07

H315 Causes skin irritation.

H313 May be harmful in contact with skin.

H333 May be harmful if inhaled.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008 Void**
- **Hazard pictograms**



GHS02



GHS05

- **Signal word** Danger

(Contd. on page 2)

Safety data sheet

According to 91/155 EEC

Printing date 08.03.2013

Vers.-Nr: 43

Revision: 02.01.2013

Trade name: Transpoxy Finish 4.60 pack B

(Contd. of page 1)

- **Hazard-determining components of labelling:**
reaction product based on fatty acids and polyethyleneamine
- **Hazard statements**
Flammable liquid and vapour.
May be harmful in contact with skin.
May be harmful if inhaled.
Causes skin irritation.
Causes serious eye damage.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures

- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Firefighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

AUS

(Contd. on page 3)

Safety data sheet According to 91/155 EEC

Printing date 08.03.2013

Vers.-Nr: 43

Revision: 02.01.2013

Trade name: **Transpoxy Finish 4.60 pack B**

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

xylene, mixture of isomers (25-50%)

NES	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 350 mg/m ³ , 80 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

AUS

Safety data sheet According to 91/155 EEC

Printing date 08.03.2013

Vers.-Nr: 43

Revision: 02.01.2013

Trade name: *Transpoxy Finish 4.60 pack B*

(Contd. of page 3)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **General Information**· **Appearance:**

Form: Fluid
 Colour: According to product specification

· **Odour:** Characteristic· **Odour threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition**

Boiling point/Boiling range: 137 °C

· **Flash point:** 30 °C· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 500 °C· **Decomposition temperature:** Not determined.· **Self-igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 7.0 Vol %

· **Vapour pressure at 20 °C:** 6.7 hPa· **Density at 20 °C:** 0.929 g/cm³· **Relative density:** Not determined.· **Vapour density:** Not determined.· **Evaporation rate:** Not determined.· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

VOC (EC) 455.2 g/l

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 5)

AUS

Safety data sheet

According to 91/155 EEC

Printing date 08.03.2013

Vers.-Nr: 43

Revision: 02.01.2013

Trade name: **Transpoxy Finish 4.60 pack B**

(Contd. of page 4)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**· **LD/LC50 values relevant for classification:***xylene, mixture of isomers*

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Strong irritant with the danger of severe eye injury.· **Sensitization:** No sensitizing effects known.

12 Ecological information

· **Aquatic toxicity:** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

· **Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**· **ADG, IMDG, IATA** UN1307· **UN proper shipping name**· **ADG** 1307 XYLENES, mixture· **IMDG, IATA** XYLENES, mixture· **Transport hazard class(es)**· **ADG, IMDG, IATA**· **Class** 3· **Label** 3· **Packing group**· **ADG, IMDG, IATA** III

(Contd. on page 6)

AUS

Safety data sheet

According to 91/155 EEC

Printing date 08.03.2013

Vers.-Nr: 43

Revision: 02.01.2013

Trade name: **Transpoxy Finish 4.60 pack B**

(Contd. of page 5)

- **Environmental hazards:**

- **Marine pollutant:** No

- **Special precautions for user**

- **Danger code (Kemler):** 30

- **EMS Number:** F-E,S-D

- **Transport/Additional information:**

- **ADG**

- **Limited quantities (LQ)** 5L

- **Transport category** 3

- **Tunnel restriction code** D/E

- **UN "Model Regulation":** UN1307, XYLENES, mixture, 3, III

15 Regulatory information

- **Australian Inventory of Chemical Substances**

All ingredients are listed.

- **Standard for the Uniform Scheduling of Drugs and Poisons**

1330-20-7 | xylene, mixture of isomers

S6

- **Labelling according to Regulation (EC) No 1272/2008 Void**

- **Hazard pictograms**



GHS02 GHS05

- **Signal word** Danger

- **Hazard-determining components of labelling:**

reaction product based on fatty acids and polyethyleneamine

- **Hazard statements**

Flammable liquid and vapour.

May be harmful in contact with skin.

May be harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Dispose of contents/container in accordance with local/regional/national/international regulations.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 7)

Safety data sheet
According to 91/155 EEC

Printing date 08.03.2013

Vers.-Nr: 43

Revision: 02.01.2013

Trade name: Transpoxy Finish 4.60 pack B

(Contd. of page 6)

*ICAO: International Civil Aviation Organization**ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent*

-AUS-