



# Rhinothane<sup>®</sup> M

## Application

- May be applied using roller
- Small areas may be coated by brush
- **Roller**                    nap size..... 5 - 6mm mohair
- **No. of coats**.....2 to 3
- **Cleaning solvent** .....T1 PU Spray Thinner

### **Caution:**

(i) This product cures by reaction with atmospheric moisture and will solidify in the can if allowed excessive contact with air. When using, remove sufficient material for the job at hand and quickly reseal; do not brush from the can; do not return unused product to the can. Unopened containers should be stable for one year, however part full containers will have limited storage stability.

(ii) Do not apply this coating when ambient temperatures are below 15° C or above 35° C or when it is extremely dry and windy because flow and cure may be adversely affected.

## Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

**Packaging Group III      UN No. 1263**

**Pack sizes            10 litre**

Authorised:      A. De Mello, Sales Manager

June 2008

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



**Wagon Paints**

**5 Stephenson Road, Bayswater North, Victoria 3153 Australia  
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au**