



T12 Gunwash

Code: THT120000

Description

- Solvent for cleaning of spray guns and other application equipment immediately after use

Properties

- Particularly effective for air-dry enamel coatings

Typical Applications

- Cleaning of spray guns, pressure pots, spray lines, paint cans, etc.
- Paint residue must still be wet; best results when applied shortly after equipment use
- Best suited to air-dry alkyds such as Zip Dry Enamel, Rapid Enamel, Purlenamel, etc.

General Data

- Recycled blend of hydrocarbon and chemical solvents

Specifications (at 25°C and 50% relative humidity)

- Appearance.....Low viscosity, clear, water-white liquid
- Specific Gravity.....0.80
- Boiling Range..... 47 - 197°C

Mixing recommendation

- Apply liberal amounts of T12 and flush through equipment or scrub with stiff bristle brush

Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

Packaging Group II UN No. 1263

Pack sizes 4 litre, 20 litre, 60 litre, 200 litre

Authorised: A. De Mello, Sales Manager

June 2008

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au