



# T4 Enamel Thinner

Code: THT40000

## Description

- Thinner for reducing enamel primers and topcoats to spray viscosity

## Properties

- Fast initial flash-off for improved vertical hold up

## Typical Applications

- Thinning of Zinc Phosphate, Shopprime and Rhinoprime primers for spray application
- Thinning of Zip Dry, Rapid, Implement Enamels, Purlenamel and Hammerdry for spray application

## General Data

- Specially formulated blend of hydrocarbon solvents

## Specifications (at 25°C and 50% relative humidity)

- Appearance..... Low viscosity, clear, water-white liquid
- Specific Gravity.....0.79
- Boiling Range..... 99 - 130°C

## Mixing recommendation

- Alkyd coatings 10 - 30% by volume
- Refer to individual Product Data Sheets for specific thinning recommendations

## Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

**Packaging Group II**      **UN No. 1263**

**Pack sizes**      1 litre, 4 litre, 20 litre, 60 litre, 200 litre

Authorised:      A. De Mello, Sales Manager

June 2008

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia  
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au