



T5 Mineral Turpentine

Code: THT50000

Description

- Thinner for reducing enamel primers and topcoats to brushing, dipping and spray viscosity

Properties

- Slower initial flash-off than T4 Enamel Thinner improves flow and reduces dry spray and blushing

Typical Applications

- Thinning of alkyd primers for brushing, dipping and spray application
- Thinning of alkyd topcoats for brushing, dipping and spray application

General Data

- Commercial mineral turpentine

Specifications (at 25°C and 50% relative humidity)

- Appearance.....Low viscosity, clear, water-white liquid
- Specific Gravity.....0.82
- Boiling Range..... 146 - 197°C

Mixing recommendation

- Spray application up to 20% by volume
- Brush application up to 10% by volume
- Dipping application up to 50% by volume

Safety precautions

- **Refer to the relevant Material Safety Data Sheet**
- Contents are flammable – keep away from all ignition sources
- Avoid contact with skin and eyes – when mixing, wear gloves and goggles
- When spraying, ensure adequate ventilation and wear appropriate protective clothing and equipment

Packaging Group III UN No. 1300

Pack sizes 1 litre, 4 litre, 20 litre, 60 litre, 200 litre

Authorised: A. De Mello, Sales Manager

June 2008

These technical data and recommendations are based on tests and information believed to be accurate at the time of printing. They should not be construed as containing any warranty, either expressed or implied. Users should conduct their own tests to determine final suitability of this product.



Wagon Paints

5 Stephenson Road, Bayswater North, Victoria 3153 Australia
Phone: 61 3 97291344 Fax: 61 3 97202179 Email: sales@wagonpaints.com.au