



Vers.-Nr: 55 Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

· Product identifier

· Trade name: Transurethane Finish 3.43 pack B

· Article number: 343b-5

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

 $\cdot \ \, \text{Application of the substance/preparation:} \\$

Hardening agent/ Curing agent

Isocyanate resin

Paint

· Details of the supplier of the safety data sheet

· Manufacturer/supplier:

Transocean Coatings

Wagon Paints Australia Pty Ltd

ABN: 76 412 791 772

Street address: 5 Stephenson Road, Bayswater North

VIC, 3153 Australia Phone: +613 9729-1344 Fax: +613 9720 2719

Emergency telephone number: Medical Emergencies: 24 Hours

Poisons Information Centre (Australia): 131 126

• •

2 Hazard Identification

· Classification of the substance or mixture

Flam. Lig. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

· Signal word Warning

(Contd. on page 2)





Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

(Contd. of page 1)

· Hazard-determining components of labelling:

Aliphatic Isocyanate xylene, mixture of isomers ethylbenzene

hexamethylene-di-isocyanate

· Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and information on ingredients

- · Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 			
28182-81-2	Aliphatic Isocya	anate	50-100%
	Skin Sens.	I, H317	
108-65-6	2-methoxy-1-m	ethylethyl acetate	10-25%
	Flam. Liq. 3	, H226	
1330-20-7	xylene, mixture		2,5-10%
	Flam. Liq. 3 Irrit. 2, H315	, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin	
100-41-4	ethylbenzene		≤ 2,5%
	Flam. Liq. 2 Tox. 4, H332	, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute	

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)





Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

No further relevant information available.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)





Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

• • • • • • • • • • • • • • • • • • • •	or parameters				
· Ingre	Ingredients with limit values that require monitoring at the workplace: 108-65-6 2-methoxy-1-methylethyl acetate				
108-€					
NES	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk				
1330-	20-7 xylene, mixture of isomers				
NES	Short-term value: 655 mg/m³, 150 ppm Long-term value: 350 mg/m³, 80 ppm				
100-4	1-4 ethylbenzene				
NES	Short-term value: 543 mg/m³, 125 ppm Long-term value: 434 mg/m³, 100 ppm				
822-0	6-0 hexamethylene-di-isocyanate				
NES	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen, as -NCO				

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)





Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

· Penetration time of glove material

(Contd. of page 4)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties					
· Information on basic physical and chemical properties					
· General Information	·				
· Appearance:					
Form: Colour:	Fluid According to product specification				
· Odour:	Characteristic				
· Odour threshold:	Not determined.				
· pH-value:	Not determined.				
· Change in condition					
Boiling point/Boiling ran	ge: 145 °C				
· Flash point:	38 °C				
· Flammability (solid, gaseo	us): Not applicable.				
· Ignition temperature:	315 °C				
· Decomposition temperatu	re: Not determined.				
· Self-igniting:	Product is not selfigniting.				
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.				
· Explosion limits:					
Lower:	1.1 Vol %				
Upper:	10.8 Vol %				
· Vapour pressure at 20 °C:	6.7 hPa				
· Density at 20 °C:	1.07 g/cm³				
Relative density	Not determined.				
Vapour density	Not determined.				
· Evaporation rate	Not determined.				
· Solubility in / Miscibility w					
water:	Not miscible or difficult to mix.				
· Partition coefficient (n-octanol/water): Not determined.					
· Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				



Safety data sheet

according to WHS Regulations

Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

(Contd. of page 5)

Solvent content:
VOC (EC)
267.5 g/l

Other information
 No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

LD/LC50 values relevant for classification:

822-06-0 hexamethylene-di-isocyanate

Oral LD50 738 mg/kg (rat)
Dermal LD50 593 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)





Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

(Contd. of page 6)

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · ADG, IMDG, IATA	UN1263
UN proper shipping nameADGIMDGIATA	1263 PAINT, special provision 640E PAINT Paint
· Transport hazard class(es)
· ADG, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
	3
 Packing group ADG, IMDG, IATA 	III
· Environmental hazards:	
· Marine pollutant:	No
 Special precautions for us Danger code (Kemler): EMS Number: Stowage Category 	ser Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
 Transport in bulk according Marpol and the IBC Code 	ng to Annex II of Not applicable.

(Contd. on page 8)





Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

(Contd. of page 6)

· Transport/Additional information:				
ADGLimited quantities (LQ)Excepted quantities (EQ)	5L Code: E1			
· Transport category · Tunnel restriction code	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/E			
· IMDG· Limited quantities (LQ)· Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml			
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640E, 3, III			

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Australian Inventory of Chemical Substances
 All ingredients are listed.
 Standard for the Uniform Scheduling of Medicines and Poisons
 1330-20-7 | xylene, mixture of isomers
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Aliphatic Isocyanate xylene, mixture of isomers ethylbenzene

hexamethylene-di-isocyanate

Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Page 9/9



Safety data sheet according to WHS Regulations

Vers.-Nr: 55 Revision: 23.05.2023

Trade name: Transurethane Finish 3.43 pack B

(Contd. of page 6)

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Lig. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· * Data compared to the previous version altered.