

Safety data sheet according to WHS Regulations

Vers.-Nr: 51


Revision: 23.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council

1 Identification

- **Product identifier**
- **Trade name:** Transvinynox HS 2.06 Hardener
- **Article number:** 206b-5
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance/preparation:**
Epoxy curing agent
Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/supplier:**
Transocean Coatings
Wagon Paints Australia Pty Ltd
ABN: 76 412 791 772
Street address: 5 Stephenson Road, Bayswater North
VIC, 3153 Australia
Phone: +613 9729-1344
Fax: +613 9720 2719
- **Emergency telephone number:**
- Medical Emergencies: 24 Hours · Poisons Information Centre (Australia): 131 126

2 Hazard Identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS02 GHS05
- **Signal word** Danger
- **Hazard-determining components of labelling:**
xylene, mixture of isomers
butan-1-ol
- **Hazard statements**
Flammable liquid and vapour.
Causes skin irritation.
Causes serious eye damage.

(Contd. on page 2)

AU

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener

(Contd. of page 1)

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

* 3 Composition and information on ingredients

- **Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene, mixture of isomers Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
71-36-3	butan-1-ol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2,5-10%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

* 4 First Aid Measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness, place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

AU
(Contd. on page 3)

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener

(Contd. of page 2)

5 Fire Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

NES	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 350 mg/m ³ , 80 ppm

(Contd. on page 4)

AU

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener

(Contd. of page 2)

71-36-3 butan-1-ol		
NES	Peak limitation: 152 mg/m ³ , 50 ppm Sk	
· DNELs		
1330-20-7 xylene, mixture of isomers		
Dermal	long term DNEL	108 mg/kg/d (General Population) 180 mg/kg/d (Workers)
Inhalative	long term DNEL	14.8 mg/m ³ (General Population) 77 mg/m ³ (Workers)
· PNECs		
1330-20-7 xylene, mixture of isomers		
PNEC STP	6.58 mg/l (water treatment plant)	
PNEC aqua	327 ug/l (freshwater) 327 ug/l (marine water)	
PNEC sediment	12.46 mg/kg (freshwater) 12.46 mg/kg (marine water)	
PNEC soil	2.31 mg/kg (Soil)	

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener

(Contd. of page 2)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: According to product specification

· Odour: Characteristic

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Boiling point/Boiling range: 205 °C

· Flash point: > 25 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 340 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.1 Vol %

Upper: 7.0 Vol %

· Vapour pressure at 20 °C: 6.7 hPa

· Density at 20 °C: 0.98847 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C: 450 mPas

Kinematic: Not determined.

· Solvent content:

VOC (EC) 358.3 g/l

(Contd. on page 6)

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener

(Contd. of page 5)

- | | |
|----------------------------|--|
| · Other information | No further relevant information available. |
|----------------------------|--|

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· LD/LC50 values relevant for classification:
--

1330-20-7 xylene, mixture of isomers

Oral	LD50	>2000 mg/kg (rat)
	LC50/ 96 hr (static)	2.6 mg/l (Rainbow trout (Oncorhynchus mykiss)) (OESO 203 or equivalent)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

- **Toxicity**

· Aquatic toxicity:

1330-20-7 xylene, mixture of isomers

EC 50 (48 hr)	1-10 mg/l (daphnia)
EC 50 (72 hr)	1-10 mg/l (Algae)

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener


(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · ADG, ADN, IMDG · IATA 	Void UN1300
<ul style="list-style-type: none"> · UN proper shipping name · ADG, ADN, IMDG · IATA 	Void Turpentine substitute
<ul style="list-style-type: none"> · Transport hazard class(es) · ADG, ADN, IMDG · Class 	Void
<ul style="list-style-type: none"> · IATA <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · Packing group · ADG, IMDG · IATA 	Void III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user 	Not applicable.

(Contd. on page 8)

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener

(Contd. of page 6)

· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

* 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Australian Inventory of Chemical Substances**

1330-20-7	xylene, mixture of isomers
-----------	----------------------------

71-36-3	butan-1-ol
---------	------------

- **Standard for the Uniform Scheduling of Medicines and Poisons**

1330-20-7	xylene, mixture of isomers	S6
-----------	----------------------------	----

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02 GHS05

- **Signal word** Danger

- **Hazard-determining components of labelling:**

xylene, mixture of isomers

butan-1-ol

- **Hazard statements**

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

- **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category** P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 9)

Safety data sheet according to WHS Regulations

Vers.-Nr: 51

Revision: 23.05.2023

Trade name: Transvinypox HS 2.06 Hardener

- (Contd. of page 6)
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- *** Data compared to the previous version altered.**